

K2 JAYMASTIC

FILLER, SEALER & GLUE FOR MABLE, GRANITE & STONE

Description:

K2 JAYMASTIC is a polyester resin based stone filler and sealer which contains premium grade raw materials that act as a long lasting adhesive for providing a strong and permanent bond to stone surface. It is meant for bonding stone to stone as well as for filling the gaps, crack and pinhole in the stone and marble for horizontal & vertical application.

Area of Application:

- K2 JAYMASTIC is used for filling the gaps, crack and pinhole in the stone, granite and marble.
- It is used for filling the joint between marble to

marble, granite to granite and stone to stone.

- It is used for fixing stone on stone.

Benefits:

- It gives excellent bonding between all types of stone joints.
- It is a quick setting marble glue which can fill the gap effectively.
- It gives long lasting, strong and permanent bonds to stone and marble surfaces.
- Easy to use.
- Joints looks beautiful and joint less.
- It gives excellent shining and polishing to any stone surface.

Technical Properties:

Properties	Results
Appearance	Viscous Liquid to Thick Paste
Variants	Solid and Liquid Variants
Color	Ivory, White and Neutral
Pot Life	3 - 7 Minutes

Application Instruction:

- Ensure that marble and stone to be rectified is dry, clean and free from dust.
- If it is necessary to correct color, use a coloring paste or a color powder.
- Take required amount of Base and mix 2 to 3 % Hardener by weight.
- Mix the base and hardener thoroughly.
- Use this mixture to fill the gaps, cracks and

pinholes of marble and stone.

Precautions:

- Always use separate spatula to take out based from the tin.
- Do not return unused mix material in tin.
- Keep Base and Hardener away from direct sunlight.
- Keep the lid of Tin and hardener tube properly shut, when not in use.

Packing:

Variants	Base -Solid	Base -Liquid	Hardener
White	1.5 Kg	1.5 Kg	45 Gm.
Ivory	1.5 Kg	1.5 Kg	45 Gm.
Neutral	1Kg	1Kg	30 Gm.

Shelf Life and Storage:

K2 JAYMASTIC has a Shelf life of 6 months for base solid & liquid variant and 6 months for Hardener from the date of manufacturing. Store the material in cool and dry place. Keep away from direct sunlight and heat.

Health & safety:

K2 JAYMASTIC is hazardous. It should not be swallowed or allowed to come into contact with the skin and eyes. Protective gloves, Nose mask and goggles should be worn. Contact

Important Note:

KONKEM Industries Private Ltd products are guaranteed against defective materials and manufacture and are sold subject to its standard terms and conditions of sale, copies of which may be obtained on request. Whilst KONKEM Industries Ltd endeavors to ensure that any advice, recommendation specification or information it may give is accurate and correct, it cannot, because it has no direct or continuous control over where or how its products are applied, accept any liability either directly or indirectly arising from the use of its products whether or not in accordance with any advice, specification, recommendation or information given by it or its applicators.

with the skin for long tenure should be avoided. In case of contact with the eyes, it should be rinsed immediately with plenty of water and medical advice sought immediately.

FIRE

K2 JAYMASTIC is flammable.

Technical Support:

The company provides a technical service supported by the team of specialist applicators in the industry.