

# K2 TILEOADD

## Liquid Additive for Tile Adhesive & Tile Grout

### Description:

K2 TILEOADD is a liquid flexible additive for use with cement slurry, tile grout and tile Adhesive. It is specially formulated to provide a strong, super flexible bond for tiling on internal and external cement surface.

### Area of Application:

- On site mix additive for fixing tile on conventional method and Leveling bed application. It is suitable for internal and external application in residential as well as commercial area like shops, malls, club houses,

country home etc.

- It is suitable to mix with cement based polymer grouts and tile adhesive for better strength.

### Benefits:

- Shock resistance with higher flexibility.
- Excellent waterproofing characteristics.
- Needs no curing and soaking of substrate or tile.
- Easy of application.
- Non-hazardous & non-flammable liquid.

### Technical Properties:

Properties	Results
Appearance	Milky White color liquid
Specific gravity	1.010
Pot life	No Significant effect
Open time	No Significant effect
Setting Time	Reduces the Setting Time
Water Demand	Reduces the water demand by 10 to 30 %
Compatibility	Compatible with K2 Newfix, K2 Unifix & K2 White GTA

### Application Instruction:

#### MIXING PROCESS

- First K2 TILEOADD to be mixed with water before adding to the tile adhesive. Approximately 10 to 30% water can be reduced depending upon dosage & tile adhesive.
- Mix with a trowel / slow speed drills (50 - 100 rpm) until a lump free homogeneous paste is obtained.
- Allow it to slake for 5 minutes.
- Mix the required quantity, which can be used within the 60 Minutes pot life.
- Additionally, it can also be used along with 1:6 cement sand mortar. Along with neat cement it can be mixed to make a slurry to fix the tiles on the floor over cement sand bedding.

### Precautions:

- Always add Powder to liquid and never add liquid to powder.
- Do not add more liquid than recommended.

### Dosage:

- 1 to 2Liter per 20 kg of Tile Adhesive.
- 1Liter per bag of cement for conventional method and cement sand mortar application.
- 200 ml/ 1 kg of K2 Colorfil TJF.

## Packing:

K2 Tileoadd is Available in 200 ml, 1 & 5 Liters Packs.

## Shelf Life and Storage:

K2 Tileoadd has a Shelf life of 12 months from the date of manufacturing. Store the material in cool and dry place. Keep away from direct sunlight and heat.

## Health & safety:

K2 TILEOADD is non-hazardous. It should not be swallowed or allowed to come into contact with the skin and eyes. Protective gloves, Nose

## Important Note:

KONKEM Industries Private Ltd products are guaranteed against defective materials and manufacture and are sold subject to its standard terms and conditions of sale, copies of which may be obtained on request. Whilst KONKEM Industries Ltd endeavors to ensure that any advice, recommendation specification or information it may give is accurate and correct, it cannot, because it has no direct or continuous control over where or how its products are applied, accept any liability either directly or indirectly arising from the use of its products whether or not in accordance with any advice, specification, recommendation or information given by it or its applicators.

mask and goggles should be worn. Contact with the skin for long tenure should be avoided. In case of contact with the eyes, it should be rinsed immediately with plenty of water and medical advice sought immediately.

## FIRE

K2 TILEOADD is non-flammable.

## Technical Support:

The company provides a technical service supported by the team of specialist applicators in the industry.

**KONKEM**  
KONKEM INDUSTRIES PVT LTD  
A Group Company of **JAY**

Jay House, Panchvati Circle,  
Ambawadi, Ahmedabad  
380006. India

Phone: 079-69073222

Email: [infok2@konkem.com](mailto:infok2@konkem.com)

Website: [www.konkem.com](http://www.konkem.com)

**TILEOADD**

