

# **K2 INSTAPLUG LD**

# Quick Setting Waterproofing & Plugging Compound

### **Description:**

K2 INSTA PLUG LD is an extra quick setting waterproofing/ plugging compound which stops running water instantly. K2 INSTA PLUG LD to be mixed with cement and sets in 2 to 4 minutes. K2 INSTA PLUG LD is an excellent time tested liquid admixture for emergency / immediate repair work due to very fast setting property.

# **Area of Application:**

K2 INSTA PLUG LD will stop running water and seepage through concrete and masonry walls, dams, and wall and floor junctions. It can be used as a grout around pipes. A plugging

compound for basements, pipe joints, retaining walls, tunnels and sewage works and quick fixing of nozzles.

#### **Benefits:**

- · Excellent quality plugging compound.
- Excellent adhesion.
- Stops running water instantly.
- · High early strength.
- · Easy to use.
- · Emergency repair work.
- · Only cement to be mixed.

# **Technical Properties:**

Properties	Results	
Appearance	Red color Liquid	
Specific Gravity	1.200	
Initial Setting Time	2-4minutes	

# **Application Instruction:**

#### **SURFACE PREPARATION**

- All surfaces to be treated must be a solid firm, dust free and clean.
- All Laitance should be removed by etching and wire-brushing.
- Surfaces contaminated with oil or grease, should be removed by using a strong industrial detergent or organic degreaser.
- A Surface should be washed thoroughly with water and dried before the application of K2 RESIBOND ER.

#### **APPLICATION PROCESS**

K2 INSTAPLUG LD should be mixed with cement and should be applied within 2 minutes, then hold and pressure should be applied for 4 minutes.

### Dosage:

30 to 40% by weight of cement. It cannot be diluted with water.

# Packing:

K2 INSTAPLUG LD is available in 1Liter & 5Liter Pack.



# **Shelf Life and Storage:**

K2 INSTAPLUG LD has a Shelf life of 24 Months from the date of manufacturing. The material should be stored between 5 °C to 40 °C and avoid exposure to sunlight.

### Health & safety:

K2 INSTAPLUG LD is not hazardous. It should not be swallowed or allowed to come into contact with the skin and eyes. Protective gloves, Nose mask and goggles should be worn. Contact with the skin for long tenure should be avoided. In case of contact with the eyes, it should be rinsed immediately with plenty of water and medical advice sought immediately.

#### Fire:

K2 INSTAPLUG LD is nonflammable.

# **Technical Support:**

The company provides a technical service supported by the team of specialist applicators in the industry.

### **Important Note:**

KONKEM Industries Private Ltd products are guaranteed against defective materials and manufacture and are sold subject to its standard terms and conditions of sale, copies of which may be obtained on request. Whilst KONKEM Industries Itd endeavors to ensure that any advice, recommendation specification or information it may give is accurate and correct, it cannot, because it has no direct or continuous control over where or how its products are applied, accept any liability either directly or indirectly arising from the use of its products whether or not in accordance with any advice, specification, recommendation or information given by it or its applicators.



Jay House, Panchvati Circle, Ambawadi, Ahmedabad 380006. India

Phone: 079-69073222

Email: infok2@konkem.com Website: www.konkem.com

