

# K2 PrimEx

## Water Thinnable High-Performance Primer

### Description:

K2 PrimEx is a water-thinnable economy primer, specially formulated to perform optimally with K2 exterior topcoats. It offers strong adhesion to exterior wall substrates, ensuring a clean, uniform, and flawless topcoat finish.

### Area of Application:

K2 PrimEx is used as a primer coat for all types of exterior, interior, vertical and horizontal

cement surface of the building.

### Benefits:

- Provides a clean, bright white finish.
- Offers good hiding power, ensuring a uniform surface for topcoat application.
- Enhances adhesion of the topcoat to the substrate, ensuring strong inter-coat bonding.
- Prevents chalking, flaking, and peeling, thereby improving the durability and adherence of the topcoat.

### Technical Properties:

Properties	Results
Appearance	White Paste
Bulk density	1.20 - 1.30 g/cc
Dry Material content, %	43 - 47 %
pH (10% Solution)	8.0 - 9.5
Surface drying time	< 30 minutes

### Application Instruction:

#### SURFACE PREPARATION

- Prepare the surface thoroughly by cleaning, washing and removing dust, dirt, oil, grease and loose particles.
- Repair the cracks up to 5 mm with K2 KRACK SEAL and above 5 mm cracks with K2 BOND SBR and modified mortar.
- All old surfaces having existing efflorescence must be thoroughly washed with water and dried before applying the product.
- Any source of water in contact with the substrate causing dampness must be closed or eliminated to avoid raising dampness from inside.

#### APPLICATION PROCESS

- For both new plastered substrates and repainting applications, apply one coat of PrimEx after diluting 1 litre of primer with 1 litre of water.

- Allow the applied coat to dry for 4–6 hours in proper sunlight conditions.

### Coverage:

7.4-9.2 sq.m/L (80-100 sq.ft/L) for 1 coat.

### Packing:

K2 PrimEx is available in 1ltr, 4 ltr, 10 ltr, 20 ltr Pack.

### Shelf Life and Storage:

K2 PrimEx has a shelf life of 18 months from the date of manufacturing. Store the material in cool and dry place. Keep away from direct sunlight and heat.

### Health & safety:

PrimEx is water based and non-toxic. Gloves should be worn during application. Any splashes on the skin or eyes must be washed off with clean water. In case of prolonged irritation seeks medical advice.

## Technical Support:

The company provides a technical service supported by the team of specialist applicators in the industry.

## Important Note:

KONKEM Industries Private Ltd products are guaranteed against defective materials and manufacture and are sold subject to its standard terms and conditions of sale, copies of which may be obtained on request. Whilst KONKEM Industries Private Ltd endeavors to ensure that any advice, recommendation specification or information it may give is accurate and correct, it cannot, because it has no direct or continuous control over where or how its products are applied, accept any liability either directly or indirectly arising from the use of its products whether or not in accordance with any advice, specification, recommendation or information given by it or its applicators.

**KONKEM**  
KONKEM INDUSTRIES PVT LTD  
A Group Company of **JAY**

Jay House, Panchvati Circle,  
Ambawadi, Ahmedabad  
380006. India

Phone: 079-69073222

Email: [infok2@konkem.com](mailto:infok2@konkem.com)

Website: [www.konkem.com](http://www.konkem.com)



**PrimEx**

#01/0126

